



# Ozone Systems

from **ClearWater Tech, LLC.**  
**800-262-0203 • 805-549-9724**  
850-E Capitolio Way, San Luis Obispo, CA 93401  
e-mail: sales@cwtozone.com • www.cwtozone.com



## Mini-Series Corona Discharge

The Mini-Series from ClearWater Tech produce more ozone using less energy than any other ozone generator available. With an ozone output range of 1.3 to 8 grams per hour, this versatile trio is like nothing else on the market today. Features include compact size, fully-adjustable ozone output, convenient electrical interface plug, and new 4-20mA control circuitry.

- 4-20mA control.
- Universal input power supply allows for input voltages from 90-260 volts, 47-63 Hz.
- All units are air cooled for ease of installation.
- All solid state electronic components for maximum longevity.
- Lowest watts-per-gram ratio of any ozone generator available.
- Convenient LED displays show variable ozone output and air dryer status.

### TYPICAL APPLICATIONS

- Residential Swimming Pools
- Commercial Spas
- Residential Well Water
- Bottled Water
- Waste Water
- Commercial Laundry
- Water Features
- Aquaculture



### CD10/AD DESCRIPTION

CD ozone generator with single reaction chamber, fully adjustable output and built-in air dryer.

### DIMENSIONS

19.5" h x 11.5" w x 5" d, 14.5 lbs

### ELECTRICAL

Universal 90/260V, 47-63 Hz, 2.2 - 0.8 amps, 200 watts

### OZONE OUTPUT

1.3 grams/hr @ 4 SCFH (dry air)  
1% concentration by weight



### CD10 DESCRIPTION

Single reaction chamber CD ozone generator with fully adjustable output. Can be used with dry air (AD-40), LPSA-20 or Workhorse 8C air preparation systems.

### DIMENSIONS

19" h x 9" w x 5" d, 9.5 lbs

### ELECTRICAL

Universal 90/260V, 47-63 Hz, 1.1 - 0.4 amps, 100 watts

### OZONE OUTPUT

1.3 grams/hr @ 4 SCFH (dry air)  
1% concentration by weight  
4 grams/hr @ 4 SCFH (PSA oxygen)  
3% concentration by weight



### CD12 DESCRIPTION

Dual reaction chamber CD ozone generator with fully adjustable output. Use with dry air (AD-40), LPSA-20, Workhorse 8C air preparation systems.

### DIMENSIONS

21.5" h x 11.5" w x 5" d, 14.5 lbs

### ELECTRICAL

Universal 90/260V, 47-63 Hz, 1.5 - 0.6 amps, 150 watts

### OZONE OUTPUT

3 grams/hr @ 8 SCFH (dry air)  
1% concentration by weight  
8 grams/hr @ 8 SCFH (PSA oxygen)  
3% concentration by weight

