

Professional Installers Want A Filter That's Easier To Install and Maintain...




The Patented TwistIIClean Delivers!

- No disassembly to clean
- Filter element flushes completely clean in less than 20 seconds
- Easy maintenance by homeowner – requires no tools, no fuss
- No need to turn off water to clean (eliminates air in system)
- Rugged design installs indoors or outdoors
- Stainless steel filter element lasts for years
- 1 year warranty

Typical Applications:

Home water well, agricultural and landscape irrigation, misting systems, pools, spas, and more!

TWISTIICLEAN Technical Specifications



----- = Not recommended at this flow

Model	Inlet/Outlet	Purge	Total Length	Length (from piping to purge port)	Width (Inlet/Outlet)
T2C-075	3/4" MPT	1/2" MPT	11 3/4"	8 3/4"	6"
T2C-100	1" MPT	1/2" MPT	11 3/4"	8 3/4"	6"
T2C-150	1 1/2" MPT	3/4" MPT	15 1/4"	11 3/4"	7 1/2"

- Mesh Size Available:
 - 30 Mesh (600 Micron) Element (Brown)
 - 60 Mesh (250 Micron) Element (White)
 - 100 Mesh (150 Micron) Element (Gray)
 - 140 Mesh (105 Micron) Element (Black)
- Pressure Rating: 100 psi (6.9 bar)
- Construction: For added durability, glass-filled polypropylene/acrylic construction with upper EPDM seal, lower Viton® seal, and stainless steel screen

TWISTIICLEAN
INLINE WATER FILTERS
LAKOS
WWW.TWISTIICLEAN.COM

Put An End To Spin-Down Filter Maintenance Hassles

Just Twist To Clean



TWISTIICLEAN
INLINE WATER FILTERS
LAKOS
WWW.TWISTIICLEAN.COM

Maintaining *Old-Fashioned* Spin-Down Filters Can Be a **BIG** hassle




Accessing the filter is a wet and dirty mess. Depressurizing the system introduces air into the system.

Filters are hard to clean and require frequent replacement.



Removing the filter bowl repeatedly will quickly wear out the top seal, causing leaks. The unit will need to be replaced.



TWIST||CLEAN is BETTER...

Just TWIST to CLEAN

Just a gentle 1/4 TWIST of the handle begins the patented **reverse flushing action**, and the TWISTICLEAN backwashes itself from inside-out. Just a few seconds later all debris are forcefully cleaned off the filter element and flushed from the bottom port.



Entire cleaning process takes less than 20 seconds

Innovative NEW Technology!

- No Mess
- No Disassembly
- No Leaks
- No Tools Required
- Rugged Design Works With All Plumbing Systems




Over 200% larger stainless steel screen area lasts for years, collects maximum debris between cleanings. Clear bowl shows when filter needs cleaning.

Patented Reverse Flushing Action

When the top handle is turned, three events take place:

- 1 Flow direction is changed to inside-out
- 2 The filter element is lifted to open the bottom flush port
- 3 An inside-out backwash occurs, and the filter element is cleaned



LAKOS Manufactures a Full Line of Patented Residential Filtration Products

SandMaster H2O/SMP

Centrifugal sand separators for residential water well sand and sediment. Flow range 5-70 gpm. Max 100 psi. Available in carbon and stainless steel.

Sand Separator ILB/ILS

Heavy duty sand separator using centrifugal separation technology. Flow range 3-290 gpm. Max 150 psi. Available in carbon and stainless steel.

Pump Protection SUB-K

Protects submersible pumps from sand damage in water wells. Reduces pump energy costs by maintaining optimum efficiency. Extends pump life by 5x or more.

Cartridge Filters CAR

LAKOS offers a line of cartridge filters for finer filtration.