

Hot Water/Chemical Resistant Sediment Filter

"Spin-Down" 3/4", 1-1/4" and 1-1/2" Hot Water Filters

The "Rusco Spin-Down" Hot Water Sediment Filters are the ideal filters to remove sediment and are cost efficient. These high quality Hot Water Filters offer years of clean water without expensive element replacement. The clear cover allows sediment to be visible and indicates when flushing is necessary. Now you can have filtered hot water with one step purging and reusable elements.



SPECIAL FEATURES

- Centrifuge Spin Down™ type sediment separation
- Flush valve allows quick one step purge cleaning
- Clear cover shows sediment collected by the screened element
- Thermoplastic construction has high chemical resistance
- Maximum pressure 150 PSI @ 73+ F (23+ C)
- Maximum temperature 200 F (93 C) @ 40 PSI
- Flow rates 1-100 gallons per minute
- Durable reusable filter elements are screened with stainless steel which is available in five mesh sizes
- No tools required as all filters parts are Hand tightened*
 only

*Using tools voids warrant


TYPES OF APPLICATIONS

- Outdoor furnaces (wood, coal or corn)
- Cooling towers
- Domestic/Commercial hot water heaters
- Heat exchangers
- Hydronic radiant floor heating systems
- Industrial (Machine Coolant and Cutting Fluids)
- Spas/Jacuzzis

Specifications



Filter Body - Polypropylene with 304 stainless steel support ring



O-Rings - Buna-N





Filter Element - Polypropylene with 316 stainless steel mesh
Mesh sizes available: 30, 60, 100, 140, 200

Flush Valve - CPVC



All Models - 10 per case Each filter individually boxed

Specifications

Part Number	* Length	Width	Flow Rate
3/4-(mesh)HT-F	11-3/8"	5" 1-25	gpm
3/4-(mesh)STHT-F	14-3/8"	5" 1-25	gpm
1-1/4-(mesh) HT-F	15-3/8"	5-1/4"	10-50 gpm
1-1/2-(mesh) HT-F	17-7/8"	5-1/2"	18-100 gpm
*Length includes Flu	ish Valve		


ALL INLETS/OUTLETS ARE FNPT ONLY

8 7 6			1-1/2" FILTER	
5 4 3 2 1	%" FILTER	1-1/4" FILTER		MIN. FLOW RATES fapplies to all models) FOR SPIN-DOWN ACTION 3/4" = 1 GPM 1-1/4" = 10 GPM 1-1/2" = 18 GPM

Rusco Filters are proudly made and assembled in the USA

MESH MICRON OPENING .021" 533 30 60 254 .010" .006" 152 100 104 .004" 140 200 74 .0029"

TEMPERATURE/PRESSURE TEMPERATURE (F*)



USING TOOLS VOIDS WARRANTY
HAND TIGHTEN ONLY



13360 Chambord Street Brooksville, FL 34613 USA 1-800-345-1033 • (352)597-2522• Fax:(352)596-9489 Email info@rusco.com Website www.rusco.com