SJE PUMPMASTER® PLUS Pump Switch

Mechanically-activated, wide-angle switch designed for direct control of pumps up to 3/4 HP at 120 VAC and 2 HP at 230 VAC.

This mechanically-activated, wide-angle pump switch provides automatic control of pumps in:

potable water

water

sewage applications

The SJE PumpMaster® Plus pump switch is not sensitive to rotation or turbulence allowing it to be used in both calm and turbulent applications.



U.S. Patent Nos. 5,087,801 & 5,142,108 SPECIFICATIONS

CABLE: flexible 14 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE)

FLOAT: 3.05 inch diameter x 3.56 inch long (7.75 x 9.04 cm) high impact, corrosion resistant, PVC housing for use in sewage and water up to 140°F (60°C)

ELECTRICAL:

120 VAC 50/60Hz Single Phase: Maximum Pump Running Current:

15 amps

Maximum Pump Starting Current:

85 amps

Recommended Pump HP:

3/4 HP or less

230 VAC 50/60Hz Single Phase:

Maximum Pump Running Current: 15 amps

Maximum Pump Starting Current:

85 amps
Recommended Pump HP:

2 HP or less

NOTE: This switch must be used with pumps that provide integral thermal overload protection.

FEATURES


- Passed NSF Standard 61 protocol by an approved Water Quality Association laboratory.
- Heavy-duty contacts.
- Controls pumps up to 3/4 HP at 120 VAC and 2 HP at 230 VAC.
- Adjustable pumping range of 7 to 36 inches (18 to 91 cm).
- Includes standard mounting clamp and boxed packaging.
- UL Recognized for use in water and sewage.
- CSA Certified.
- Three-year limited warranty.














OPTIONS

This switch is available:

- for pump down or pump up applications as specified by part number.
- with a 120 VAC or 230 VAC piggy-back plug.
- without a plug for direct wiring in 120 VAC or 230 VAC applications.
- in standard cable lengths of 10, 15, 20, or 30 feet and 3, 5, 6, or 10 meters (longer lengths available).



PO Box 1708, Detroit Lakes, MN 56502 1-888-DIAL-SJE • 1-218-847-1317 1-218-847-4617 Fax email: sje@sjerhombus.com

www.sjerhombus.com