CWS Static Mixers PVC



Excellent for instant mixing of injected chemicals such as chlorine, soda ash, or sodium hydroxide for water treatment

- Industrial Quality Inline static mixer
- PVC slip Unions on each end, no threaded available
- Glue-type slip fittings for easy installation into PVC pipe
- The mixer has NO moving parts.


The mixer will instantaneously and completely mix any combination of gas or liquid with the water stream.

The unique baffle design continues to redivide and recombine the streams as it passes through, generating a lot of turbulence, ensuring complete mixing with no energy, moving parts and very low pressure loss.



- Maximum pressure 110 PSI
- Heavy-duty Gray Sch 40 PVC
- Not NSF Certified
- Pressure Drop (water) 2 PSI min flow 15 PSI max flow
- Made in China
- Warranty 1 Year

| Model | Pipe Size | L1 mm | L2 mm | L1 Inches | L2 Inches | Gallons/Minute Minimum | Gallons/Minute Maximum |
|----------|-----------|-------|-------|-----------|-----------|---------------------------|---------------------------|
| M8000560 | 3/4" | 330 | 225 | 13 | 8.8 | 2.5 | 8 |
| M8000540 | 1" | 420 | 292 | 16.5 | 11.5 | 4 | 14 |
| M8000550 | 1 1/2" | 565 | 406 | 22.25 | 16 | 9.5 | 44 |
| M8000580 | 2" | 695 | 497 | 27.5 | 19.5 | 15.5 | 88 |



Call toll-free: 1-888-600-5426 Email us: support@cleanwaterstore.com Clean Water Systems & Stores Inc 2806-A Soquel Ave Santa Cruz CA 95062